PUSH-IN TYPE HIGH PRESSURE MALE CONNECTORS
PUSH-IN TYPE HIGH PRESSURE 90º MALE ELBOWS

The new ***Dropsa High Pressure Push-in Fittings*** for oil and grease offer key benefits:

- **Lower part cost when compared to existing compression fittings**
- **Fast clamping of tube into fitting drastically reduces assembly time**
- **Reduced Maintenance cost from quick substitution**

The ***Dropsa High Pressure Push-in Fittings*** are available in different types.

Easily assembled and disassembled; there is no wear or damage to the tubes as previously experienced with conventional & push-in fittings.

CHARACTERISTICS

- **MATERIAL: BRASS**
- **TUBE: NYLON, RILSAN, POLYAMIDE, POLYETHYLENE, POLYURETHAN**
- **DIAMETERS: ∅ 4 - ∅ 6**
- **FLUID: OIL, GREASE**
- **WORKING TEMPERATURE : - 10°C ÷ +80°C (+14°F ÷ +176°F)**

CONTACTS

www.dropsa.com
sales@dropsa.com

ITALIA
Dropsa SpA
t. +39 02-250791
f.+39 02-25079767

U.K.
Dropsa (UK) Ltd
t. +44 (0)1784-431177
f. +44 (0)1784-438598

GERMANY
Dropsa GmbH
t. +49 (0)211-394-011
f. +49 (0)211-394-013

FRANCE
Dropsa Ame
t. +33 (0)1-3993-0033
f. +33 (0)1-3986-2636

U.S.A.
Dropsa Corporation
t. +1 586-566-1540
f. +1 586-566-1541

AUSTRALIA
Dropsa Australia Ltd.
t. +61 (02)-9938-6644
f. +61 (0)2-9938-6611

BRAZIL
Dropsa Brasil Ind.e Com.Ltda
t. +55 (0)11-563-10007
f. +55 (0)11-563-19408

CHINA
Dropsa Lubrication Systems (Shanghai) Co., Ltd
t. +86 (021) 67740275
f. +86 (021) 67740205

STRAIGHT

Ø Tube 4		
Part No.	Thread	Max. Pressure (bar)
3084579	M 6 x 1	65
3084631	M 6 x 0,75	65
3084577	1/8 BSP	65
3084682	5/16 – 24 UMF	65

Ø Tube 6		
Part No.	Thread	Max. Pressure (bar)
3084587	1/8 NPT	65
3084578	1/8 BSP	65
3084609	1/4 BSP	65
3084753	M 6 x 1	250

90°

Ø Tube 4		
Part No.	Thread	Max. Pressure (bar)
3084630	M 6 x 0,75	65
3084650	M 6 x 1	65
3084653	M 8 x 1	65
3084654	M 10 x 1	65
3084580	1/8 BSP	65
3084588	1/8 NPT	65

Ø Tube 6		
Part No.	Thread	Max. Pressure (bar)
3084581	1/8 BSP	65
3084610	1/4 BSP	65
3084589	1/8 NPT	65

90° SWIVEL

Ø Tube 4		
Part No.	Thread	Max. Pressure (bar)
3084613	M 6 x 1	65
3084611	5/16-24 UNF	65
3084620	1/8 NPT	65
3084638	1/8 BSP	65
3084731	M 8 x 1	150
3084696	1/8 BSP	150

Ø Tube 6		
Part No.	Thread	Max. Pressure (bar)
3084695	1/8 BSP	150
3084750	1/4 BSP	150
3084751	M 6 x 1	150
3084752	M 8 x 1	150