

SMART 2



Oil lubrication pumps for Orifice (01) and Injector (33V) Lubrication Systems



Automatic Lubrication Systems

GB
USA
SMART 2

OIL LUBRICATION PUMPS for Orifice (01) and Injector (33V) Lubrication Systems



The SMART2 range oil lubrication pumps provides innovative pump packages for the machine tool industry. The SMART2 Electric Gear Pump has been designed for systems with a working pressure of up to 30 bar.

The pumps are available either with a built in controller card which controls the entire system or the manual version can be connected to a separate control device.

It is suitable for systems requiring flow rates of up to 100cm³/min and pressure of up to 30 bar.

Innovative pump package for the machine tool industry

All units are fitted as standard with built in Pressure switch, Low Level Switch and Pressure Gauge.

TECHNICAL CHARACTERISTICS				
Reservoir Capacity	3 lt (0.66 galls) in oil-proof transparent plastic			
Compatible lubricants	Mineral oil			
Storage temperature	- 20°C ÷ + 60°C (-4°F ÷ +140°F)			
Electrical power	110 / 230 V AC 50 Hz 110 / 230 V 60 Hz			
Absorbed consumption	110V/50Hz	110V/60Hz	230V/50Hz	230V/60Hz
	162W	155W	150W	148W
Pump flowrate	110V/50Hz	110V/60Hz	230V/50Hz	230V/60Hz
	180 cm ³ /min (10,98 cu.in.)/min	220 cm ³ /min (13,45 cu.in.)/min	180 cm ³ /min (10,98 cu.in.)/min	220 cm ³ /min (13,45 cu.in.)/min
Max. pressure	30 bar (441psi)			
Lubricant viscosity (Working temperature)	68 ÷ 320 cSt (320 ÷ 1480 SUS)			
Working temperature	+ 5°C ÷ + 60°C (+41°F ÷ +140°F)			
Working humidity	90% max relative humidity			
Mechanical Protection Grade	IP 55			
Pressure sound continuous level	< 70 dB (A)			

ORDERING INFORMATION	
Codice	Descrizione
3600240	Manual SMART2 110V /50 Hz
3600241	Manual SMART2 110V / 60Hz
3600242	Manual SMART2 230V / 50 Hz
3600243	Manual SMART2 230V / 60 Hz
3600210	Automatic SMART2 110V / 50 Hz
3600211	Automatic SMART2 110V / 60 Hz
3600212	Automatic SMART2 230V / 50 Hz
3600213	Automatic SMART2 230V / 60 Hz



Features

- **Cycle time: 10 seconds to 2 minutes (10 seconds increments).**
- **Pause Time: 1 minute to 60 hours (1 minute increments).**
- **Cycle and Level monitoring capabilities.**
- **LCD Display for easy operation and setting.**
- **External Cycle Counting Capability .**
- **Suspend function (pause and cycle).**

Web site:
<http://www.dropsa.com>

E-mail:
sales@dropsa.com

WK 28/07
C2001PE

ITALY
Dropsa SpA
t.(+39) 02-250791
f.(+39) 02-25079767

CHINA
Dropsa Lubrication Systems
Tel: +86 (021) 67740275
Fax: +86 (021) 67740205

U.S.A.
Dropsa Corporation
t.(+1) 586-566-1540
f.(+1) 586-566-1541

U.K.
Dropsa (UK) Ltd
t.(+44) 01784-431177
f.(+44) 01784-438598

BRAZIL
Dropsa
t.(+55) 011-563-10007
f.(+55) 011-563-19408

GERMANY
Dropsa GmbH
t.(+49) 0211-394-011
f.(+49) 0211-394-013

AUSTRALIA
Dropsa Australia Ltd.
t.(+61) 02-9938-6644
f.(+61) 02-9938-6611

FRANCE
Dropsa Ame
t.(+33) 01-3993-0033
f.(+33) 01-3986-2636