

GREASE GUNS



GREASE SPRAY GUN 1527174

Grease spray gun F/160 SP HPS 2,2

This spray gun has been specifically designed to spray grease with viscosity up to NLGI 2. The air and grease volumes can be individually adjusted. The maximum air pressure is of 4 bar. The maximum grease pressure is of 250 bar.



NOZZLES 1527175

Nozzles kit for grease spray gun HPS 1,9



NOZZLES 1527091

Nozzles kit for grease spray gun HPS 2,2



NOZZLES 1527092

Nozzles kit for grease spray gun HPS 2,5



RUBBER 1527189

Rubber hoses kit 2SC 1/4" – R6 5/16" | 5,0 m



RUBBER 1527093

Rubber hoses kit 2SC 1/4" – R6 5/16" | 10,0 m
Composed by 1 high pressure grease hose and 1 hose R6 for air, both hoses are protected by the same reinforced case.



PRESSURE REGULATOR 1527176

Pressure regulator with connections for MEC SPRAY
Maximum pressure: 4 bar



GREASE GUNS 1527078

GREASE GUN NO TUBE F1/4"



GREASE GUNS 1527080

GREASE GUN FLEXIBLE HOSE F1/4" 400 MM



GREASE GUNS 1527171

GREASE GUN FLEXIBLE HOSE F1/4" 400 MM
SWIVELLING



GREASE GUNS 1527083

GREASE GUN FLEXIBLE HOSE F1/4" 400 MM
TRIPLE-SWIVELLING



GREASE GUNS 1527084

GREASE GUN RIGID TUBE F1/4" 200 MM
SWIVELLING



GREASE GUNS 1527086

GREASE GUN RIGID TUBE F1/4" 200 MM
SWIVELLING



GREASE GUNS 1527088

GREASE GUN RIGID TUBE F1/4" 200 MM
TRIPLE-SWIVELLING



GREASE GUNS 1527079

GREASE GUN NO TUBE F3/8"

GREASE GUNS 1527081

GREASE GUN FLEXIBLE HOSE F3/8" 400 MM

GREASE GUNS 1527082

GREASE GUN FLEXIBLE HOSE F3/8" 400 MM
SWIVELLING

GREASE GUNS 1527172

GREASE GUN FLEXIBLE HOSE F3/8" 400 MM
TRIPLE-SWIVELLING

GREASE GUNS 1527085

GREASE GUN RIGID TUBE F3/8" 200 MM
SWIVELLING

GREASE GUNS 1527087

GREASE GUN RIGID TUBE F3/8" 200 MM
SWIVELLING

GREASE GUNS 1527089

GREASE GUN RIGID TUBE F3/8" 200 MM
TRIPLE-SWIVELLING



DIGITAL GREASE GUN 1527090

Digital Grease Gun F1/4" G

Composed by:

Digital meter 4 digits

Triple-swivelling joint

Rigid end + 4-jaws coupling

Not approved for public use

Part Number		1527090
Flow-rate	gpm	0,003-0,66
Inlet connection	BSP	F 1/4" G
Outlet connection	BSP	F 10X1
Max air pressure	bar	500
Burst pressure	bar	1000
Batch meter	cipher	4
Totalizing meter in kg	cipher	4
Working temperature	max C°	60°
Battery life	months	24

DIGITAL GREASE GUN 1527077

Pneumatic nozzle for grease R = 50:1

500 cc with rigid tube and jaws coupling

Suitable for Ø 52 mm 400 g cartridge

Suitable for the distribution at high pressure of all kinds of grease

The operating pressure for the grease pumps may vary between a minimum of 3.5 bar and a maximum of 8.5 bar.

Part Number		1527077
Flow-rate	g/cycle	0,68
Compression ratio	bar	50:1
Air consumption	l/min	130
Air inlet connection	BSP	F 1/4" G
Grease outlet connection	M	F 10x1
Grease delivery @6 bar	g/min	1500
Noise level	dB	80
Tank capacity	g	500
Inside diameter of chamber	mm	54
For cartridge ø 52mm	g	400

